



# Ball Valves - LEADED Brass



## Forged LEADED Brass Full Port Ball Valve Features:


- Heavy pattern forged leaded brass construction.
- Full port allows maximum flow & minimum pressure drop or turbulence.
- PTFE seats, chrome plated brass ball.
- PTFE stem packing with adjustable gland follower.
- Blow out proof stem design.
- 600 PSI W.O.G. non-shock; 150 PSI S.W.P. (400 PSI 2 1/2", 3" 4")
- CSA Certified (TxT only), UL Listed.



### MATERIAL SPECIFICATIONS

Handle nut	Zinc Coated Steel
Handle	Zinc Coated Steel
Gland Follower	Forged Brass
Stem Packing	PTFE
Ball	Chrome Plated Brass
Seats	PTFE
Body	Forged Brass
End Adapter	Forged Brass

Part Number	Threaded	Size	Ctn/Case Qty	List Price Threaded	Part Number	List Price Sweat
HFBV6-25T		1/4"	50/100	\$ 11.17		
HFBV6-38T		3/8"	50/100	10.79		
HFBV6-50T		1/2"	50/100	15.82	HFBV6-50S	\$ 12.90
HFBV6-75T		3/4"	30/60	22.33	HFBV6-75S	21.75
HFBV6-100T		1"	20/40	35.73	HFBV6-100S	29.93
HFBV6-125T		1- 1/4"	12/24	56.77	HFBV6-125S	49.56
HFBV6-150T		1-1/2"	9/18	84.80	HFBV6-150S	74.43
HFBV6-200T		2"	6/12	127.18	HFBV6-200S	97.11
HFBV6-250T		2-1/2"	3/6	265.38		
HFBV6-300T		3"	2/4	371.02		
HFBV6-400T		4"	2	682.37		



### MATERIAL SPECIFICATIONS

Handle nut	Zinc Coated Steel
Handle	Zinc Coated Steel
Gland Follower	Forged Brass
Stem Packing	PTFE
Ball	Chrome Plated Brass
Seats	PTFE
Body	Forged Brass
End Adapter	Forged Brass

## Forged LEADED Brass FULL Port Ball Valve with Hose Barbs Features:

- Heavy pattern, full port, forged leaded brass construction.
- PTFE seats, chrome plated brass ball.
- PTFE stem packing with adjustable gland follower.
- Blow-out proof stem design.
- 600 psi W.O.G. non-shock; 150 psi S.W.P.
- Insert hose barb ends for use with polyethylene pipe connections.



Part Number	Size	Ctn/Case Qty	List Price
HFBV6-50I	1/2"	50/100	\$ 13.90
HFBV6-75I	3/4"	30/60	21.65
HFBV6-100I	1"	20/40	47.19
HFBV6-125I	1-1/4"	12/24	68.07



HGBVL Series

ISO 9001

## Forged Brass Gas Ball Valve Features:

- Heavy duty two piece forged brass body.
- For use with natural, manufactured, mixed, liquified petroleum and LP gas/air mixtures.
- Meets ANSI standard Z21.15 for use as a gas appliance connector valve (1/2 lb. system). CSA, US/AGA B-16.44
- Pressure rated at 175 psi W.O.G. non-shock.
- Imported, Mfg for American Granby in an ISO 9001 facility.



### MATERIAL SPECIFICATIONS

Handle Screw	Steel
Handle	Aluminum
Stem O-Rings	NBR
Stem	Forged Brass
Ball	Chrome Plated Brass
Seats	PTFE
Body	Forged Brass
End Adapter	Forged Brass

DIMENSIONS (IN.)	BTU Capacity/Hr.			
	SIZE	A	B	C
1/2"	2.21	1.46	1.81	295,000
3/4"	2.38	1.75	1.81	795,000
1"	2.91	1.89	1.81	1,200,000

Part Number	Size t x t	Ctn/Case Qty	List Price
HGBVL50T	1/2"	12/144	\$ 12.78
HGBVL75T	3/4"	12/96	19.04
HGBVL100T	1"	6/96	22.63



In the United States: Phone (800) 776-2266 Fax (800) 729-3299  
 In Canada: Phone (800) 268-7570 Fax (905) 629-3204

www.americangranby.com

6/3/19