

# **Detectable Warning Tape Product Specifications**

## **Product Type**

Detectable Warning Tape

# Description

• Detectable warning tape provides for easy buried pipeline detection and below ground identification and warning. The tape can be located below ground with a non-ferrous metal locator/detector when buried at the proper depths. We recommend bury depths

•	Tape Width	2"	3"	6"
	<b>Burial Depth</b>	6" - 18"	6" - 28"	6" - 36"

#### **Standard Widths**

• 2", 3", 6", 12"

# **Standard Length**

• 1000'

# **Physical Properties**

Elongation: 80% MD and 135% TD

.0020 aluminum core adhered to 2.55 polyethylene backing

Tape color and legend combination are in accordance with APWA requirements

Tensile Strength: 7,800 PSI

Made in USA

Tape printing beneath top protective layer

• Thickness: 5 mil nominal

Ultra high molecular weight

• 100% virgin polyethylene

Alkaline and corrosion resistant

Heavy metal free

APWA color coded

### Packaging

• 2" - 12 rolls per case

• 3" – 8 rolls per case

• 6" – 4 rolls per case

12"- 2 rolls per case

## Legends

•	Blue	Caution Buried Water Line Below
•	Blue	Caution Buried Geothermal Line Below
•	Brown	Caution Buried Non-Potable Water Line Below
•	Green	Caution Buried Sewer Line Below
•	Orange	Caution Buried Fiber Optic Line Below
•	Orange	Caution Buried Telephone Line Below
•	Red	Caution Buried Electric Line Below
•	Red	Caution Buried High Voltage Cable Below
•	Yellow	Caution Buried Gas Line Below
•	Purple	Caution Buried Reclaimed Water Line Below