



CODE	Weight lbs/pc	Volume ft ³ /pc	ND	OD	S min	L1	Thread	LTh. min	L2	L
12EIRPEAFM0101SSNPT	0.282	0.0059	1" IPS	1.315	0.120	3.90	1" NPT	0.75	2.00	5.90
12EIRPEAFM114114SSNPT	0.485	0.0132	1 1/4" IPS	1.660	0.151	5.70	1 1/4" NPT	0.75	2.60	8.30
12EIRPEAFM112112SSNPT	0.586	0.0173	1 1/2" IPS	1.900	0.173	5.70	1 1/2" NPT	0.75	2.60	8.30
12EIRPEAFM0202SSNPT	0.959	0.0291	2" IPS	2.375	0.216	5.30	2" NPT	0.94	3.50	8.90
12EIRPEAFM0303SSNPT	2.094	0.0617	3" IPS	3.500	0.318	4.60	3" NPT	1.22	4.00	8.70
12EIRPEAFM0404SSNPT	3.922	0.1477	4" IPS	4.500	0.409	8.60	4" NPT	1.34	4.00	12.60

EloFIT



AMERICAS

ITEM:
12EIRPEAFM_SSNPT

C:\Vault_Temp\Disegn\Shede Tecniche\Elofit inches\Transition fittings\EL10341.dwg

DESC: PE/STAINLESS STEEL THREADED ZINC
COATED TRANSITION FITTINGS
PE4710 SDR11



DRAWING No:

EL10341

SHEET OF REV.

1 1 -4

www.nupiamericas.com - info@nupiamericas.com

All dimensions have to be considered in inches with 5% tolerance if not otherwise mentioned