

ACCESSORIES: FLOWMETERS

410N IN-LINE FLOWMETER FEATURES

- Tough machined acrylic meter body, highly polished to a clear finish
- Direct reading permanent scale
- White back reflector for easy reading
- Sturdy adapters with high grade FKM o-ring seals
- 316 stainless steel float guide rods
- Acceptable in direct sunlight applications

410N SERIES IN-LINE FLOWMETER SPECIFICATIONS

- Max. Working Pressure - 150 psig (10.3 bar) @ 70° F (21° C)
- Max. Fluid Temperature - 150° F (65° C) @ 0 PSI
- Full scale accuracy - +/- 5%
- Meter body material - Machined acrylic

410N Series

Part Number	GPM	LPM	Connection
F40750LN-12	1.0 to 10	4.0 to 38	3/4" FPT
F40750LN-16	1.0 to 10	4.0 to 38	1" FPT
F41000LN-12	2.0 to 20	8.0 to 80	3/4" FPT
F41000LN-16	2.0 to 20	8.0 to 80	1" FPT



410N SERIES

451 & 452N IN-LINE FLOWMETER FEATURES

- Polysulfone meter body resists high temperatures and pressures
- 316 SS rod guided float
- Direct reading permanent scale
- Not recommended for direct sunlight

451 & 452N SERIES IN-LINE FLOWMETER SPECIFICATIONS

- Max. Working Pressure - 150 psig (10 bar) @ 70° F (21° C)
- Max. Fluid Temperature - 212° F (93° C) @ 0 PSI
- Full scale accuracy - +/- 3%
- Meter body material - Polysulfone

451 / 452N Series

Part Number	GPM	LPM	Connection
F451003LHN	3.0 to 30	10 to 110	1" FPT
F451004LHN	4.0 to 40	15 to 155	1" FPT
F452060LH	6.0 to 60	30 to 230	2" FPT



451 / 452 SERIES

Call for availability of other sizes.



ALL THE "PUMP" YOU NEED AND MORE

27

1-866-646-6724
712-652-3424
www.bdmfginc.com